

## Product Data Sheet

### **KORLUBE® ATF MULTI-VEHICLE FULLY SYNTHETIC**

#### **Full Synthetic Automatic Transmission Fluid**

#### **Product Description**

**KORLUBE®** ATF MULTI-VEHICLE FULLY SYNTHETIC is a full synthetic automatic transmission fluid, specially formulated to provide excellent performance and protection for a wide range of Asian, North American and European vehicles.

#### **Features & Benefits**

##### **HIGH PERFORMANCE**

- Excellent thermal and oxidation stability keeps transmission clean to help provide outstanding performance even under severe driving conditions.
- Excellent frictional properties help to improve transmission efficiency and smooth shifting performance.

##### **HIGH PROTECTION**

- Excellent low-temperature fluidity helps to provide immediate protection at starting in cold weather.

##### **LONG TRANSMISSION LIFE**

- Excellent frictional properties help to extend transmission life.
- Outstanding anti-wear properties helps to reduce wear which leads to extend transmission life.

##### **LONG FLUID LIFE**

- Excellent oxidation stability helps to extend fluid life.
- Outstanding shear stability helps to keep viscosity even under severe heavy duty and high temperature operating conditions.

##### **SAVE FUEL**

- Excellent frictional properties help to consume less fuel.

#### **Applications**

- Asian Vehicles including Toyota, Hyundai, Kia, Mitsubishi, Honda, Nissan, Subaru, Isuzu, Suzuki, Mazda, Daihatsu
- American Vehicles including GM, Ford
- European Vehicles using Aisin Automatic Transmissions including Volkswagen, Volvo, Porsche, Opel, Renault, Fiat

## Specifications

**KORLUBE®** ATF MULTI-VEHICLE FULLY SYNTHETIC meets or exceeds the requirements of the following specifications :

	ATF MULTI-VEHICLE FULLY SYNTHETIC
TOYOTA TYPE T-IV, AUTO FLUID D-II, D-III	√
HYUNDAI SP-III	√
KIA SP-III	√
MITSUBISHI SP-II, SP-III	√
HONDA ATF Z-1	√
NISSAN MATIC FLUID C, D, J	√
SUBARU ATF	√
ISUZU BESCO ATF-II, ATF-III	√
SUZUKI ATF	√
MAZDA ATF M-III, M-V	√
DAIHATSU AMMIX ATF D3-SP	√
GM DEXRON DEXRON-II, IID, IIE, III, IIIG, IIHH	√
FORD MERCON	√
ALLISON C-4	√
JASO M315 TYPE 1A	√

## Typical Properties

	ATF MULTI-VEHICLE FULLY SYNTHETIC
Viscosity @100°C, cSt	7.3
Viscosity @40°C, cSt	35.1
Viscosity @-30°C, cP	3,120
Viscosity Index	180
Flash Point, °C	216
Pour Point, °C	- 50
Density @15°C, g/cm <sup>3</sup>	0.860
Color	RED

## Health & Safety

This product is not expected to produce adverse effect on health when used for the intended application and recommendations. Do not use for the purpose other than its intended application. When disposing of used product, please take care to protect the environment.