

## Product Data Sheet

### **KORLUBE® ATF TYPE SP-III FULLY SYNTHETIC**

#### **Full Synthetic Automatic Transmission Fluid**

#### **Product Description**

**KORLUBE®** ATF TYPE SP-III FULLY SYNTHETIC is a full synthetic automatic transmission fluid, specially formulated to provide optimum performance and protection for the automatic transmissions requiring Hyundai SP-III and Kia SP-III.

#### **Features & Benefits**

The full synthetic formula of **KORLUBE®** ATF TYPE SP-III FULLY SYNTHETIC is designed to provide excellent performance and protection for the automatic transmissions requiring Hyundai SP-III and Kia SP-III. These outstanding performance and protection capabilities translate into significant benefits, including :

##### **HIGH PERFORMANCE**

- Excellent thermal and oxidation stability keeps transmission clean to help provide outstanding performance even under severe driving conditions.
- Excellent controlled friction properties help to improve transmission efficiency and smooth shifting performance.

##### **HIGH PROTECTION**

- Excellent low-temperature fluidity helps to provide immediate protection at starting in cold weather.

##### **LONG TRANSMISSION LIFE**

- Excellent controlled friction properties help to extend transmission life.
- Outstanding anti-wear properties help to reduce wear which leads to extend transmission life.

##### **LONG FLUID LIFE**

- Excellent oxidation stability helps to extend fluid life.
- Outstanding shear stability helps to keep viscosity even under severe heavy duty and high temperature operating conditions.

##### **SAVE FUEL**

- Excellent controlled friction properties help to consume less fuel.

#### **Applications**

- Automatic transmissions requiring Hyundai SP-III and Kia SP-III

**Specifications**

**KORLUBE®** ATF TYPE SP-III FULLY SYNTHETIC meets or exceeds the requirements of the following specifications :

ATF TYPE SP-III FULLY SYNTHETIC	
HYUNDAI SP-III	√
KIA SP-III	√

**Typical Properties**

ATF TYPE SP-III FULLY SYNTHETIC	
Viscosity @100°C, cSt	7.3
Viscosity @40°C, cSt	35.1
Viscosity @-30°C, cP	3,120
Viscosity Index	180
Flash Point, °C	216
Pour Point, °C	- 50
Density @15°C, g/cm <sup>3</sup>	0.860
Color	RED

**Health & Safety**

This product is not expected to produce adverse effect on health when used for the intended application and recommendations. Do not use for the purpose other than its intended application. When disposing of used product, please take care to protect the environment.