

Product Data Sheet

KORLUBE [®] EURO FORMULA ECO FULLY SYNTHETIC

Advanced Full Synthetic Motor Oil

Product Description

KORLUBE® EURO FORMULA ECO FULLY SYNTHETIC is an advanced full synthetic motor oil, specially formulated for the most stringent standards of European vehicles manufacturers including Volkswagen, BMW, Mercedes-Benz and Porsche.

It is fully compatible with Diesel Particulate Filter (DPF) and Gasoline Catalytic Converter (CAT), and provides exceptional performance, protection and cleaning power in conjunction with fuel economy. It also helps to extend the life and maintain the efficiency of emission systems.

KORLUBE® EURO FORMULA ECO FULLY SYNTHETIC 5W30 is officially certified by the American Petroleum Institute (API) as "Resource Conserving" engine oils which meet the International Lubricant Specification Advisory Committee (ILSAC) GF-5 standard for excellent fuel economy and engine protection.

KORLUBE® EURO FORMULA ECO FULLY SYNTHETIC is available with 2 multi-viscosity grades : 5W-30 and 5W-40.

Features & Benefits

LONG EMISSION SYSTEM LIFE

- Low ash content helps to reduce particulate build up in Diesel Particulate Filter (DPF).
- Low sulfur and phosphorous content helps to reduce poisoning of Gasoline Catalytic Converter (CAT).

LONG ENGINE LIFE

- Advanced full synthetic formula helps to prevent deposits and sludge build-up to enable long and clean engine life.
- Quick engine starting in cold weather and ultra fast protection helps to extend engine life.

LONG OIL LIFE

- Excellent thermal and oxidation stability prevents oil breakdown and maintains oil viscosity, which helps to reduce oil aging and to extend oil change intervals.

SAVE FUEL

- Enhanced low friction properties helps to enhance fuel economy.

SAVE EARTH

- Specially engineered additive package system helps to reduce exhaust gas emission.



Applications

KORLUBE® EURO FORMULA ECO FULLY SYNTHETIC is recommended for all types of modern automobile engines, especially the high performance and latest gasoline and diesel passenger vehicles equipped with DPF and CAT and requiring the belowmentioned specifications.

Specifications

- KORLUBE® EURO FORMULA ECO FULLY SYNTHETIC has official OEM approvals for : VOLKSWAGEN VW 502.00, VW 505.00, VW 505.01
- It meets or exceeds the requirements of the following specifications :

	5W-30	5W-40
ACEA C3		\checkmark
ACEA C2	\checkmark	\checkmark
ACEA A5/B5	\checkmark	\checkmark
API SN	\checkmark	\checkmark
ILSAC GF-5	\checkmark	
MB 229.31		\checkmark
MB 229.51		\checkmark
MB 229.52		\checkmark
VOLKSWAGEN VW502.00	\checkmark	\checkmark
VOLKSWAGEN VW505.00	\checkmark	\checkmark
VOLKSWAGEN VW505.01		\checkmark
BMW LONGLIFE-04	\checkmark	\checkmark
PORSCHE	\checkmark	\checkmark
JAGUAR LAND ROVER ST JLR.03.5004		\checkmark
FORD WSS-M2C948-B	\checkmark	\checkmark
VOLVO CAR VCC RBS0-2AE	\checkmark	\checkmark
PSA PEUGEOT CITROEN B712290		\checkmark
GM DEXOS 2	\checkmark	\checkmark

Typical Properties

	5W-30	5W-40
ACEA	C3, A5/B5	C3, A5/B5
API	SN	SN
Viscosity @100°C, cSt	10.6	14.9
Viscosity @40°C, cSt	64.5	99.5
Viscosity Index	154	157

KORLUBE [®]

PDS : KORLUBE® EURO FORMULA ECO FULLY SYNTHETIC

Flash Point, °C	226	230
Pour Point, °C	- 40	- 40
Density @15°C, g/cm3	0.855	0.855

Health & Safety

This product is not expected to produce adverse effect on health when used for the intended application and recommendations. Do not use for the purpose other than its intended application. When disposing of used product, please take care to protect the environment.