

Product Data Sheet

KORLUBE® GL-4 75W-85W

High Performance Automotive Gear Lubricant

Product Description

KORLUBE® GL-4 75W-85W is a high performance automotive gear lubricant, specially formulated to provide optimum performance and protection for front wheel drive (FWD) vehicle's manual transmission.

Features & Benefits

LONG GEAR LIFE

- Excellent wear protection helps to extend gear life.
- Outstanding rust and corrosion protection of copper help to extend gear life.
- Optimized friction properties help to extend gear life.
- Excellent thermal, oxidation and shear stability help to extend gear life.

LONG OIL LIFE

- Excellent oxidation and thermal stability helps to extend oil life.
- Outstanding shear stability helps to keep viscosity even under severe conditions.

SAVE FUEL

- Optimized friction properties help to consume less fuel.

Applications

All front wheel drive (FWD) vehicle's manual transmission requiring API GL-4

Specifications

KORLUBE® GL-4 75W-85W meets or exceeds the requirements of the following specifications :

GL-4 75W-85W	
API GL-4	√

Typical Properties

GL-4 75W-85W	
API	GL-4

Viscosity @100°C, cSt	12.1
Viscosity @40°C, cSt	66.5
Viscosity Index	182
Flash Point, °C	224
Pour Point, °C	- 45
Density @15°C, g/cm3	0.862

Health & Safety

This product is not expected to produce adverse effect on health when used for the intended application and recommendations. Do not use for the purpose other than its intended application. When disposing of used product, please take care to protect the environment.